CITY OF HIALEAH INVITATION FOR BIDS BID NUMBER 522

The Department of Grants and Human Services of the City of Hialeah, Florida, will receive sealed bids for the property located at 4531 WEST 14 COURT., HIALEAH, FLORIDA, owned by ARIEL DE ARMAS under the project entitled: SHIP PROGRAM until 11:00 A.M. on FRIDAY, JUNE 23, 2017, at the Hialeah City Hall, 501 Palm Avenue, First Floor, Department of Grants and Human Services, Hialeah, Florida, at which time all bids will be publicly opened and read aloud.

A PRE-BID MEETING HAS BEEN SCHEDULED FOR THE PROJECT ON: FRIDAY, JUNE 9, 2017 at 9:30 A.M. NOTE: FOR YOUR BID TO BE ACCEPTABLE, IT IS MANDATORY THAT YOU ATTEND THE PRE-BID MEETING FOR THIS PROJECT.

Bids sent through the United States Postal Service should be addressed to the City of Hialeah Department of Grants and Human Services Housing Programs, P.O. Box 110040, Hialeah, Florida 33010-0040, with the lower left-hand corner of the envelope marked "Sealed bids" and the bid number, address, client's name and date and time of bid opening. Please ensure the envelope/bids are securely "sealed." Bid on items and amounts of work of materials listed on work write-up sheets only. This will ensure that you are not bidding on more work or materials than other bidders. If you have any questions regarding this bid you may contact our office at (305) 883-8040, TDD number for hearing impaired (305) 883-5886.

ALL PRICES MUST BE TYPED OR IN BLUE INK AND BID MUST BE PROPERLY SIGNED AND DATED.

Attention is called to the fact that this is a federal funded program and that the contractor must ensure that employees and applicants for employment are not discriminated against because of their age, race, color, religion, sex, disability, national origin, or familial status.

The City of Hialeah provides equal access and equal opportunity in employment and services. Section 3 Businesses, Minority and Women owned businesses are encouraged to apply.

The City of Hialeah housing staff reserves the right to reject any and all bids or to waive any informalities in the bidding process. Bids may be held by the City of Hialeah for a period not to exceed thirty (30) days from the date of the opening of bids for the purpose of reviewing the bids and investigating the qualifications of the bidders prior to awarding the contract. The final determination of the contractor selection will be based on the lowest acceptable and responsive bid.

SPECIAL NOTE: If you have not already done so, with your proposal you must submit copies of your State and County's contractor's license, insurance, non-collusion affidavit, and a completed application which can be picked up at the address listed above.

CITY OF HIALEAH, FLORIDA

NOTICE TO ALL CONTRACTORS PARTICIPATING UNDER THE CITY OF HIALEAH REHABILITATION PROGRAM

A PREBID MEETING HAS BEEN SCHEDULED AT THE FOLLOWING PROPERTY:

CASE NUMBER:

S-510

OWNER: ARIEL DE ARMAS

ADDRESS:

4531 WEST 14 COURT, HIALEAH, FLORIDA

PHONE: (786) 391-4132 DATE: JUNE 9, 2017 TIME:

9:30 A.M.

IT IS MANDATORY THAT YOU OR YOUR REPRESENTATIVE ATTEND THIS PRE-BID MEETING IN ORDER TO SUBMIT A BID ON THIS PROJECT. ALL THOSE IN ATTENDANCE WILL BE ASKED TO SIGN A FORM TO CONFIRM THEIR PRESENCE AT THE PRE-BID MEETING. ONLY THOSE CONTRACTORS THAT HAVE SIGNED OFF ON THE FORM WILL BE AUTHORIZED TO BID ON THE PROJECT.

THE CITY OF HIALEAH HOUSING PROGRAM INSPECTOR AND THE PROPERTY OWNER WILL BE AVAILABLE DURING THIS MEETING TO REVIEW THE WORK WRITE-UP AND ANSWER ANY QUESTIONS YOU MAY HAVE REGARDING THE REHABILITATION SCHEDULED AT THIS PROPERTY.

THIS WILL BE YOUR OPPORTUNITY TO THOROUGHLY INSPECT THE HOUSE AND BRING UP ANY POTENTIAL PROBLEMS, COST ISSUES, ADDITIONAL WORK WHICH MAY BE REQUIRED, ETC. PLEASE NOTE THAT CHANGE ORDERS WILL NOT BE PROCESSED FOR THESE PROJECTS AND THAT THE PRODUCT SPECIFIED ON THE WORK WRITE-UP MUST BE INSTALLED. OR EQUAL ITEMS WILL NOT BE ACCEPTED UNLESS STATED ON THE WORK WRITE-UP. IT IS YOUR RESPONSIBILITY TO THOROUGHLY INSPECT THE HOME AND MAKE SURE ALL POTENTIAL PROJECT COST ARE INCLUDED IN BID.

THE NUMBER FOR THE BUILDING DEPARTMENT IS (305) 883-5825.

IF YOU HAVE ANY QUESTIONS, PLEASE CONTACT THE DEPARTMENT OF GRANTS AND HUMAN SERVICES AT (305) 883-8040.

SHNOTCON

Address Description Report

Addresses

4531 W 14 Court

Hialeah, FL 33013

Project Type: Single Family Selective Rehab

Owner: ARIEL DE ARMAS

Structure Type: Single-Family Attached

Neighborhood:

Parcel:

Client Number: S-510

Project Mgr:

SPECS BY LOCATION/TRADE

6/2/2017

Bidd Bidd	re-Bid Site Visit: Case Numbe ling Open Date: Project Manage ling Close Date: Phone Initial: Unit: U	r:			
Location:	1 - General Requirements Approx. Wa	all SF: 0		Ceiling/Floor S	F: 0
Spec #	Spec	Quantity	Units	Unit Price	Total Price
Trade: 1	General Requirements		***************************************		
1.1	CONTRACTOR JOB LIMIT	1.00	EA	n/a	n/a
1.1	New contractors who have not performed work under this program will have a one (1) job limit. When this job has been successfully completed to the satisfaction of the City and the Owner, the Contractor will be subject to a three (3) job limit. Jobs will be awarded to the next lowest acceptable bidder, when the low bidder has three project underway.		L/ \	1974	Tira
1.10	COST ALLOWANCES When specifications in the work write up refer to cost allowance the contractor is to permit the homeowner to select the product to be installed, providing th pre-tax cost of the product that does not exceed the allowance. the product selected must mee the quality standards specified in this Work Write Up.	1.00	EA	n/a	n/a
1.11	WORKMANSHIP AND MATERIAL STANDARD Contractor to peform work specified in Work Write Up in a high quality good workmanlike manner using specified materials or approved equals. Material must also 1) be of high quality, 2) be installed in accordance with manufacturer's specs and 3) meet requirements of code enforcement inspectors. All "equals" must be approved by Program Director. Final descision on workmanship willbe by the Program Field Specialist.	1.00	EA	n/a -	n/a - ·
1.12	WORK SCHEDULE Contractor shall complete at contract signing a work progress schedule form to be provided by Program Director.	1.00	EA	n/a	n/a
1.13	PROGRAM INSPECTIONS Contractor shall call Field specialist for inspection of all work that will be concealed from view following completion of work on that item. For example, these inspections frequently include, but are not limited to 1) inspection of footings, 2) inspection of roof sheathing prior to installation of felt and shingles 3) inspection between coats of paint and 4) inspection of repaired floors prior to installation of new subfloor, underlayment and floor coverings. Building Department inspections shall be as per South Florida Building Code. Work that has been concealed without a compliance inspection may result in payment delays and denials.	1.00	EA	n/a	n/a
1.14	BUILDING DEPARTMENT INSPECTIONS Building Department inspections are required in addition to Rehabilitation Program Specifications. Contractor shall be responsible for requesting all mandatory inspections as per FBC	1.00	EA	n/a	n/a
1.15	PAYMENT REQUEST	1.00	EA	n/a	n/a

Addres	s: 48	531 W 14 Court Unit:	Unit 01	3-11-211-11-11-11-11-11-11-11-11-11-11-11		
Locatio	Ď:	1 - General Requirements Approx. V	Vall SF: 0		Ceiling/Floor S	F: 0
Spe	c#	Spec	Quantity	Units	Unit Price	Total Price
Trade:	1	General Requirements				H
		Request for contract payment shall be accepted in the following manner: Up to \$10,000 - one payment at 100% completion of work \$10,001 to \$50,000 - one payment at 30% completion of work, one payment at 60% completion of work, and final payment at 100% completion of work.	g			
1.16		CHANGE ORDERS Change orders will only be approved for life safety and/or code requirements and may not exceed 10% of the approriate line item cost to include profit and overhead unless waived by the Program Director. Change orders must be approved by the Program Director in advance in writing. You are required to obtain a minimum of three estimates for any proposed change order unless waived by the Director. Please attach a detail breakdown for labor and materials. Change orders will be included in permit document revisions.	1.00	EA	n/a	n/a
1.17		PROGRESS AND FINAL PAYMENT INSPECTIONS Contractor must submit to Program Director a payment request signed by the homeowner approving payment in addition to releases of liens and warranties. This request must be submitted at least two days ahead of desired inspection date.	1.00 t	EA	n/a	n/a
1.18		PROTECT HOUSE FROM DAMAGE DURING WORK Contractor shall take steps to protect the home and contents from damage during the project. Contractor is advised to use drop cloths to protect furniture, appliances, entertainment systems, and other house contents and components. Contractor shall move furniture and appliances out off and backinto work areas once work is complete. Contractor not to leave furniture, appliances, clothing or other house contects unprotected outside during the job. Contractor shall be responsible for rain water damage to the interior of the house and it's contents while performing a roof improvement.		EA	n/a	n/a
1.19		REPAIR DAMAGE CAUSED TO PROPERTY DURING WORK Contractor is responsible for professionally repairing or replacing building and site components damaged as a result of construction activity or negligence.	1.00	EA	n/a	n/a
1.2		PERMITS The City of Hialeah will pay for the contractor's primary building permit fee. The Contractor shall obtain and pay for all other required permits and fees including specialty permits such as plumbing, electrical, roofing, HVAC, mechanical, and any other required permits and post on site all permits and licenses necessary to complete the project. Contractor and subcontractors must have current licenses required by the State, County or City.	1.00	EA	n/a	n/a
1,20		PAINT AND PRIMER All paint and primer used shall have a minimum of 15 years manufacturer warranty. Color to be selected by owner. Two coats required. Inspection between coats required by the Field Specialist.	1.00	EA	n/a	n/a
1.21		LEAD BASED PAINT AND LEAD SAFE WORK PRACTICES	1.00	EA	n/a	n/a

Address: 4	531 W 14 Court Unit:	Unit 01			
Location:	1 - General Requirements Approx. V	Vall SF. 0		Ceiling/Floor S	E: 0
Spec #	Spec	Quantity	Units	Unit Price	Total Price
Trade: 1	General Requirements				
	If a property is found to contain lead based paint and federal funds are used to pay for the project, the contractor must comply with the federal requirements under 24 CFR Part 35, and any other applicable federal, state or local regulations. Contractor must be certified in Lead Safe Work Practices in order to work on homes containing lead based paint. The cost of the initial clearance test will be paid by the City of Hialeah. If the contractor fails initial clearance testing, the contractor shall pay the cost of the additional clearance testing until the property passes clearance.				
1.22	PRODUCT APPROVALS All items required shall have Miami-Dade County approvals.	1.00	EA	n/a	n/a
1.23	CONCEAL ANY NEW WIRING AND PLUMBING LINES FROM VIEW All new electrical wiring and plumbing lines are to be installed concealed from view inside stud walls, under floors and in attics Unless otherwise approved by the homeowner and the Program Director and Code. Wiring should be concealed. Where it is not possible to conceal electrical wiring as listed and approved, surface raceway system will be permitted.		EA	n/a	n/a
1.24	REDUCE AIRBOURNE DUST DURING CONSTRUCTION Contractor to take the steps necessary to reduce and contain airbourne dust created during construction, demolition and removal of defective paint. Wet scrape if removing defective paint. Do not use electrical sanders, or torches if removing paint. Contractor and workers encouraged to wear protective clothing and respirators and to follow hygiene procedures approved by OSHA.	1.00	EA	n/a	n/a
1.3	FPL INCENTIVE PROGRAM WEATHERIZATION PROGRAM Customer agrees to apply for participation in the Florida Power and Light incentive program.	1.00	EA	n/a	n/a
1.4	CODE COMPLIANCE Contractor is responsible for code compliance. All materials and methods of construction related to work performed on this project must comply with locally adopted code requirements and must meet the approval of local code enforcement officials.	1.00	EA	n/a	n/a
1.5	CUSTOMER TO BOX UP BREAKABLES the customer is responsible for boxing up and protecting any breakable items.	1.00	EA	n/a	n/a
1.6	CUSTOMER TO HELP CLEAN UP EACH DAY The customer is responsible for helping the contractor keep the house and yard orderly during construction.	1.00	ΕA	n/a	n/a
	JOB SITE WORK WRITE UP A job copy of the permit document and permit card shall be posted near the front door. this permit document shall be sued by all inspectors and other interested parties to review scope of work and work being performed on project.	1,00	EA	n/a	n/a
	PLACE A JOB SIGN IN FRONT YARD Contractor shall securely position a project sign in the front yard and within view of the street. It is the contactor's responsibility	1.00	EA	n/a	n/a

Address	4531 W 14 Court	Unit: Unit 01			
Location	1 - General Requirements	Approx. Wall SF: 0		Ceiling/Floor S	3F: 0
Spec	# Spec	Quantity	Units	Unit Price	Total Price
Trade: 1	General Requirements				
	to pick a sign up from and return it to the Program Administrator. Signs to be returned in good condition	on.			
1.9	CONTRACTOR TO VERIFY MEASUREMENTS, S QUANTITIES All measurements, sizes and quantities and feasibil Work Write Up are approximate. The contractor is for verifying exact measurements, sizes and quantit	ity in this responsible	EA	n/a	n/a
	feasibility prior to submitting a quote. Contractor sh to the Program Manager any discrepancies which w a change to the specifications prior to submitting his	all forward ould requrie			
10	Exhibit 1. After careful review the applicant understance accepts the work described & has initialed & dated this WWU.	Jp (WWU) rred to as ands &	DU		
	XxX				
14	CONTRACTOR ACCEPTS SCOPE OF WORK The undersigned contractor certifies that he/she has reviewed & agrees to perform the work described in Write Up (WWU) with the "Date Inspected" date of	this Work	DU	New 2012	printerior con contrata a servicio
		ctor shall			
120	FINAL CLEAN Remove from site all construction materials, tools ar Sweep clean all exterior work areas. Vacuum all interareas, removing all visible dust, stains, labels and tar all windows referenced in specifications.	erior work	RM	Management	
141	HURRICANE PROTECTION Contractor shall be responsible for protecting job site prior to hurricane. Watch as declared by the U.S. We Bureau.		GR		
		L	ocatio	ı Total;	
ocation:	2 - Site work	Approx. Wall SF: 0	(Ceiling/Floor SI	=: 0 -,
Spec #	Spec	Quantity	Units	Unit Price	Total Price
rade: 5	Demolition & Disposal			THE STATE OF THE S	
750	DEMO AND REMOVE REAR ROOF STRUCTURE Demolish and remove rear roof structure. The contra protect and secure from damage all other structures, paved areas, shrubbery, and lawn areas. Repair affect to match existing as close as possible.	sidewalks,	SF	AND THE REAL PROPERTY OF THE P	-
785	CUT CONCRETE TO PROVIDE 30% GREEN AREA	1.00	ΕA		

Address:	4531 W 14 Court	nit: Unit 01			
Location:	2 - Site work Appr	ox. Wall SF: 0		Ceiling/Floor S	F: 0
Spec #	Spec	Quantity	Units	Unit Price	Total Price
Trade: 5	Demolition & Disposal				
	Cut concrete to provide 30% of green. Backfill and install gin affected areas. See Survey	gravel			
Trade: 10	Carpentry				
3005	INSTALL ACCORDION SHUTTERS Furnish and install Miami-Dade County Approved according shutters on all windows, glass doors and glass openings. Building Permit, shop drawings approval and inspections required. ONLY FOR REAR KITCHEN WINDOW AND SLIDING GLASS DOOR IN DINING ROOM.	1.00 on	EA		Allahaman (Allahaman)
4305	GENERAL CARPENTRY WORK	1.00	EA		
	Remove burglars bars and repair affected areas to match existing as close as possible.				
Trade: 15	Roofing				
4550	INSTALL NEW BUILT-UP ROOF WITH GRANULATED CAPSHEET COVERING Remove and properly dispose of existing roof covering down deck; replace all damaged sheathing and renail entire sheat to current Florida Building Code (FBC). Present 8d shank a o.c. Include a secondary water barrier. Reinforce or replaced damaged rafters with a minimum No. 2 Southern Yellow Pi Verify 5/8" plywood sheathing and-renail with 8d ring shank When renailing GC is to make sure there is no no shinners the in the attic. Also verify that there is no existing shiners. Replace damaged overhang wood under soffit and fascia, replace any damaged soffit screen. It is the contractor's responsibility to ensure that roof work, installation and mate comply with current FBC. Required inspections to be reque at appropriate intervals. Install built-up roof according to current FBC Chapter 34, Notice of Acceptance and /or Miami-Dade County Application Protocols. Paint all new wood with a cool-base primer followed by additional coats of oil-base or lapaint of good quality. Prepare galvanized metal drip for pair by first cleaning metal with an adequate solution to clean manufacture residue then apply a galvanized metal primer coat followed by additional coats of oil-base or latex paint or good quality. Roofing contractor must provide minimum 7 ywarranty on all work. INCLUDE INSTALLING TAPERED INSULATION.	athing at 6" at 6" ne. in erials ested rent at of attex ating base f	EA	n/a	n/a
Trade: 22	Plumbing				
7165	FURNISH AND INSTALL VACCUM BREAKERS Furnish and install vaccum breakers at all existing hose bible Repair affected areas to match existing as close as possible Materials and method to meet Florida Building Code.		EA		44-
Trade: 23	Electric				
7470	REPLACE ELECTRIC SERVICE 150 AMP	1 00			

Address:	4531 W/14 Court	Unit: Unit 01			
Location:	2 - Site work	Approx. Wall SF: 0		Ceiling/Floor S	SF: 0
Spec #	Spec	Quantity	Units	Unit Price	Total Price
Trade: 23	Electric				
	Dispose of old electric service to code legal dump. install a new 150 amp single phase, 3 wire electric Include a main disconnect, new circuit panel with scircuits to supply load and provide two spares for finew meter socket, new riser with weather head, se two ground rods and grounding electrode conducte load calculation and riser diagram to substantiate the installed. Properly seal all service raceway penetra all affected areas to match existing as close as possible materials and method to meet Florida Building Cod RELOCATE SERVICE FROM UTILITY ROOM AN NEW METER CAN AND MAIN DISCONNECT.	service. sufficient sufficient suture growth, strvice cable, or. Provide a she service tion. Repair ssible.			
7640	INSTALL A NEW WEATHERPROOF GFCI RECE Furnish and install a 15 amp, ground fault interrupted receptacle in a weatherproof non-ferrous box or not using an approved wiring method with 14 AWG copy conductors. Receptacle cover shall be of the type the weatherproof when a cord is attached and shall be connected to box. Materials and method to meet Figurial Building Code. One in front and one in rear.	er protected n-metallicbox oper nat is permantently	EA		
8160	INSTALL A NEW ENTRANCE LIGHT Furnish and install an exterior, waterproof, wall moubulb fixture outside exterior door. Include wire box, switch and lamp. All materials and method to meet Building Code. IN REAR.	wire, interior	EA		N
		ı	_ocatio	n Total:	
Location:	3 - Interior	Approx. Wall SF: 0		Ceiling/Floor SI	F: 0
Spec #	Spec	Quantity	Units	Unit Price	Total Price
Trade: 19	Paint & Wallpaper				
5486	PAINT CEILING WITH FLAT PAINT	1.00	EA	n/a	n/a
	Apply 1 coat of primer and 2 coats of flat acrylic late: ceiling surfaces and, if applicable, 2 coats of semi-gl paint on any wood ceiling trim. Use stain killer and processary. Wet scrape any defective paint and repart or cracks in ceiling surfaces prior to painting. Owner color. Field inspectionrequired in between coats. INCREPLACING DRYWALL WHERE NEEDED AND REPOPCORN TO MATCH EXISTING AS CLOSE AS F	oss acrylic rimer if ir any holes to select SLUDE EPAIR			٠,
5489	PREPARE AND PAINT ALL EXISTING WOOD DOO JAMB AND CASING If necessary, scrape and sand wood door, jamb and Secure loose materials and caulk all cracks prior to a primer. Apply primer that bonds to bare wood and ex Then apply two coats of semi-gloss acrylic latex pain and paint to be applied using a roller or brush—spray not permitted. Primer and paint to be high quality and year manufacturer's warranty. Owner to select color of	casing. pplying isting paint. t. Primer painting have a 15	EA	n/a	n/a

	4531 W 14 Court	Unit: Unit 01				
Location	3 - Interior	Approx. Wall SF:	0	100 100 100 100 100 100 100 100 100 100	Ceiling/Floor S	SE: 0
Spec	# Spec	Quan	tity	Units	Unit Price	Total Pri
Γrade: 1	9 Paint & Wallpaper					
5491	PAINT WALL SURFACES WITH FLAT PAIN' WITH SEMI-GLOSS PAINT		.00	EA	n/a	r
	Apply one coat of primer and two coats of flat to wall surfaces and two coats of semi-gloss a to trim which includes any baseboard, door carwindow casing, sills, stools, and sashes. When scrape defective paint, spot prime, seal water cracks or holes to walls and baseboard. Make is securely fastened to wall. Caulk cracks in baintersection with wall surfaces using mildew reto painting. Field inspection required between a specialist. Owner to select on color of paint for color for trim.	crylic latex paint sing and jambs, e applicable, wet stains, and repair sure baseboard seboard and at sistant caulk prior coats by Field				
rade: 23	Electric					
7567	CHECK ALL OUTLETS Electrical contractor shall check all outlets throu for correct polarity and grounding. If grounding are installed, an equipment grounding conductor provided. If an equipment grounding cannot be ground fault circuit interrupter protection (GFCI) provided to supply grounding type receptacles of the supply grounding type receptacles.	ughout the house type receptacles or must be provided , then shall be	00	EA	n/a	n
	provided to supply grounding type receptacies t	ALLICH SHOW DO				
	marked "GFCI Protected" and "No Equipment (406.3 (D)(3)(C). Repair affected areas to match close as possible. All outlets must work properly method to meet Florida Building Code.	existing as				
	406.3 (D)(3)(C). Repair affected areas to match close as possible. All outlets must work properly method to meet Florida Building Code.	existing as	Lo	catio	n Total:	-
	406.3 (D)(3)(C). Repair affected areas to match close as possible. All outlets must work properly method to meet Florida Building Code. 4 - Entry Hall	existing as	Lo		n Total: Ceiling/Floor SI	- -: 0
ocation: Spec#	406.3 (D)(3)(C). Repair affected areas to match close as possible. All outlets must work properly method to meet Florida Building Code. 4 - Entry Hall	existing as		(
Spec #	406.3 (D)(3)(C). Repair affected areas to match close as possible. All outlets must work properly method to meet Florida Building Code. 4 - Entry Hall Spec Carpentry	existing as Materials and Approx. Wall SF: 0 Quanti		(Ceiling/Floor SI	
Spec #	406.3 (D)(3)(C). Repair affected areas to match close as possible. All outlets must work properly method to meet Florida Building Code. 4 - Entry Hall Spec	existing as Materials and Approx. Wall SF: 0 Quanti	ty ((Ceiling/Floor SI	
Spec #	406.3 (D)(3)(C). Repair affected areas to match close as possible. All outlets must work properly method to meet Florida Building Code. 4 - Entry Hall Spec Carpentry INSTALL A NEW PREHUNG 6-PANEL INSULA DOOR WITH LOCKS Furnish and install a new pre-hung 1-3/4" thick 6	existing as Materials and Approx. Wall SF: 0 Quanti TED METAL 1.0	ty (Units (Ceiling/Floor SI	
ide: 10	406.3 (D)(3)(C). Repair affected areas to match close as possible. All outlets must work properly method to meet Florida Building Code. 4 - Entry Hall Spec Carpentry INSTALL A NEW PREHUNG 6-PANEL INSULA DOOR WITH LOCKS Furnish and install a new pre-hung 1-3/4" thick 6 insulated metal door unit including jamb, casing plate, threshold and weatherstripping and with cl	existing as Materials and Approx. Wall SF: 0 Quanti TED METAL 1.0 -panel hinges, striker hain door stop.	ty (Units (Ceiling/Floor SI	
Spec#	406.3 (D)(3)(C). Repair affected areas to match close as possible. All outlets must work properly method to meet Florida Building Code. 4 - Entry Hall Spec Carpentry INSTALL A NEW PREHUNG 6-PANEL INSULA DOOR WITH LOCKS Furnish and install a new pre-hung 1-3/4" thick 6 insulated metal door unit including jamb, casing plate, threshold and weatherstripping and with clinstall view scope and a new entry and single cylinstall v	existing as Materials and Approx. Wall SF: 0 Quanti TED METAL 1.0 -panel hinges, striker hain door stop, inder deadbolt	ty (Units (Ceiling/Floor SI	
Spec#	406.3 (D)(3)(C). Repair affected areas to match close as possible. All outlets must work properly method to meet Florida Building Code. 4 - Entry Hall Spec Carpentry INSTALL A NEW PREHUNG 6-PANEL INSULA DOOR WITH LOCKS Furnish and install a new pre-hung 1-3/4" thick 6 insulated metal door unit including jamb, casing plate, threshold and weatherstripping and with clinstall view scope and a new entry and single cyllocketset keyed alike and manufactured by Kwik Weiser or approved equal. Caulk, prime and approved equal. Caulk, prime and approved equal.	existing as Materials and Approx. Wall SF: 0 Quanti TED METAL 1.0 -panel hinges, striker hain door stop, inder deadbolt set, Yale, ly two coats of	ty (Units (Ceiling/Floor SI	
Spec#	406.3 (D)(3)(C). Repair affected areas to match close as possible. All outlets must work properly method to meet Florida Building Code. 4 - Entry Hall Spec Carpentry INSTALL A NEW PREHUNG 6-PANEL INSULA DOOR WITH LOCKS Furnish and install a new pre-hung 1-3/4" thick 6 insulated metal door unit including jamb, casing plate, threshold and weatherstripping and with clinstall view scope and a new entry and single cyllocketset keyed alike and manufactured by Kwik: Weiser or approved equal. Caulk, prime and apphigh quality oil-base paint on door, jamb and cas have a high quality factory paint finish do not required.	existing as Materials and Approx. Wall SF: 0 Quanti ATED METAL 1.0 -panel hinges, striker hain door stop inder deadbolt set, Yale, ly two coats of ling. Doors that dire painting	ty (Units (Ceiling/Floor SI	
Spec#	406.3 (D)(3)(C). Repair affected areas to match close as possible. All outlets must work properly method to meet Florida Building Code. 4 - Entry Hall Spec Carpentry INSTALL A NEW PREHUNG 6-PANEL INSULA DOOR WITH LOCKS Furnish and install a new pre-hung 1-3/4" thick 6 insulated metal door unit including jamb, casing plate, threshold and weatherstripping and with clinstall view scope and a new entry and single cyllocketset keyed alike and manufactured by Kwiki Weiser or approved equal. Caulk, prime and apphigh quality oil-base paint on door, jamb and cas have a high quality factory paint finish do not requiless requested by the owner. Owner to select color. Door must have N.O.A. from Miami-Dade I	Approx. Wall SF: 0 Quanti ATED METAL 1.0 -panel hinges, striker hain door stop inder deadbolt set, Yale, ly two coats of ing. Doors that uire painting, door paint Product	ty (Units (Ceiling/Floor SI	
Spec#	406.3 (D)(3)(C). Repair affected areas to match close as possible. All outlets must work properly method to meet Florida Building Code. 4 - Entry Hall Spec Carpentry INSTALL A NEW PREHUNG 6-PANEL INSULADOR WITH LOCKS Furnish and install a new pre-hung 1-3/4" thick 6 insulated metal door unit including jamb, casing plate, threshold and weatherstripping and with clinstall view scope and a new entry and single cyllocketset keyed alike and manufactured by Kwiki Weiser or approved equal. Caulk, prime and apphigh quality oil-base paint on door, jamb and cas have a high quality factory paint finish do not requinless requested by the owner. Owner to select color. Door must have N.O.A. from Miami-Dade I Approval Section. INCLUDE SIDE LITE SO IT C.	Approx. Wall SF: 0 Quanti ATED METAL 1.0 -panel hinges, striker nain door stop. inder deadbolt set, Yale, ly two coats of ing. Doors that uire painting, door paint Product AN MATCH	ty (Units (Ceiling/Floor SI	
Spec#	406.3 (D)(3)(C). Repair affected areas to match close as possible. All outlets must work properly method to meet Florida Building Code. 4 - Entry Hall Spec Carpentry INSTALL A NEW PREHUNG 6-PANEL INSULA DOOR WITH LOCKS Furnish and install a new pre-hung 1-3/4" thick 6 insulated metal door unit including jamb, casing plate, threshold and weatherstripping and with clinstall view scope and a new entry and single cyllocketset keyed alike and manufactured by Kwiki Weiser or approved equal. Caulk, prime and apphigh quality oil-base paint on door, jamb and cas have a high quality factory paint finish do not requiless requested by the owner. Owner to select color. Door must have N.O.A. from Miami-Dade I	Approx. Wall SF: 0 Quanti ATED METAL -panel hinges, striker nain door stop. inder deadbolt set, Yale, ly two coats of ing. Doors that uire painting, door paint Product AN MATCH K. GLASS TO H THE	ty (Units (Ceiling/Floor SI	F: 0 Total Pric

Address	:: 4531 W 14 Court	Unit: Unit 01			
Location	ı: 4-Entry Hall	Approx. Wall SF: 0		Ceiling/Floor S	SF: 0
Spec	# Spec	Quantity	Units	Unit Price	Total Price
Trade:	22 Plumbing				· · · · · · · · · · · · · · · · · · ·
7091	1 INSTALL A NEW TANKLESS WATER HE Remove existing water heater. Furnish and tankless water heater. Provide proper plum connections. Install unit as per manufactur meets enough capacity to cover th size of affected areas to match existing finish as a Electrician is to consult with FPL prior to indiscuss the load of the tankless water. All r to meet Florida Building Code.	d install a new Titan hbing and electrical e specification and it the house. Repair close as possible. stallation in order to	EA	n/a	n/a
Trade: 2	23 Electric				
7810	INSTALL A NEW SMOKE AND CARBON COMBO DETECTORHARD WIRED Furnish and install a UL approved, ceiling r smoke and carbon monoxide combo detect back-up. Smoke detector outlets in bedroof protected. Materials and method to meet Fi	nounted, hard wired tor with battery ms must be AFCI	EA		-
			Locatio	n Total:	
Location	5 - Bathroom 1	Approx Wall SF: 0	ur Jakon	Ceiling/Floor S	:F::::0
Spec		Quantity	Units	Unit Price	Total Price
Frade: 2			<u> </u>		*
7590	INSTALL A NEW RECEPTACLEGFCI BA	ATH 1.00	EA		
	Furnish and install a flush mounted, ground interrupted duplex receptacle and cover pla circuit, adjacent to the basin using approved Conductors must be copper. Fish wire nece openings. To match surrounding finish as of Materials and method to meet Florida Buildi	fault circuit te feed by 20 amp d wiring method. essary and repair lose as possible.			
		ι	ocatio	n Total:	······································
ocation:	6 - Living Room	Approx. Wall SF: 0		Ceiling/Floor S	F: 0
Spec #		Quantity	Units	Unit Price	Total Price
rade: 10	Carpentry				
2953	INSTALL A NEW SINGLE HUNG WINDOW MATCH EXISTING Dispose of existing window. Furnish and ins match existing window finish. If window to be 48" of an exterior door in closed position, the tempered glass. Include removable scren. T manufactures specification and product contant sash finish to match remaining windows	tall a new window to e installed is within e window is to be to meet trol approval. Frame	EA	n/a	n/a

Addres	ss: 4	531 W 14 Court Unit:	Unit 01		7	
Locatio	on:	6 - Living Room Approx. V	Vall SF; 0		Ceiling/Floor S	F: 0
Spe	ec#	Spec	Quantity	Units	Unit Price	Total Price
Trade:	10	Carpentry				-
		Inspection has been performed.) Building Permit and inspection is required. TO BE HIGH IMPACT RESISTANT. MATCH THE WINDOWS TO THE REST OF THE COMPLEX AS CLOSE AS POSSIBLE WITH TRIM MOLDING OR ANYTHING POSSIBLE MAYBE ASSOCIATION HAS A INFO ON IT.	6			
			ļ	_ocatio	n Total:	Hamman bearing a bearing and a bearing a
Locatio	n:	7 - Kitchen Approx. N	/all SF: 0		Ceiling/Floor S	F: 0
Spe	c #	Spec	Quantity	Units	Unit Price	Total Price
Trade:	10	Carpentry				
3376	6	INSTALL A NEW WOOD PANEL TYPE BI-FOLD DOOR Furnish and install a new 1-1/8" thick, wood panel type bi-fold door with metal track and all hardware in existing opening. Stair door or prime and paint door with two coats of semi-gloss acrylic latex paint. Doors that have a high quality factory paint finish do not require painting, unless requested by the homeowner. Owner to select color of finish.	1.00	EA	n/a	n/a
3745		INSTALL NEW WALL AND BASE KITCHEN CABINETS Remove and properly dispose of existing kitchen cabinets in disrepair and furnish and install a new one. Repair and paint all affected areas to match existing as close as possible. Base, upper cabinets and backsplash shall be plastic laminate clad 1/32" min thickness, with appropiatedoors and drawers. Counte top shall be 3/4" plywood "Virola" grade or equal, approx 25" wide with full backsplash plastic laminate 1/16" min thickness for counter top. Backsplash, toe kick and cabinet interior base floor shall be 5/8" plywood "Virola" grade wood or equal. Counter top shall be 3/4" plywood, "Virola" grade wood or equal. Base cabinet to have 1/2" shelves. Include pair of drawers hardware, catches and pulls of good quality and design as per mfrs specifications. Owner to select plastic laminate. NOTE: Contractor shall repair, paint or match any affected area by the removal or replacement of the kitchen cabinets and/or counter tops. (All areas, floors, walls, or ceilings affected by cabinet removals must be filled in level of existing surfaces, using comparable materials and sealing of areas to roach and rodent proof, prior to installing cabinets). Replace any rotten drywall prior to cabinet installation. Materials and method to meet Florida Building Code.		EA		
rade: 2 6835	22	Plumbing FURNISH AND INSTALL A NEW DOUBLE BOWL SINK AND	1.00	ΕA		
0000		FAUCET Install a 33"x22"x6" double bowl, stainless steet, self rimming kitchen sink including a steet, metal body single control faucet and spray with a 15 year drip- free warranty, trap, supply lines, and shut-off valves. Faucet to have a maximum flow of 2 gallons per minute. Price Pfister, Delta, Glacier Bay, American Standard, Moen or approved equal. Materials and method to	1.00			

Addre	er i besket da. Gregoria (d. 1814)					en amazza a Marana a la	
Location)n:	7 - Kitchen	Approx V	Vall SF: 0		Ceiling/Floor	SF: 0
Spe	ec#	Spec		Quantity	Units	Unit Price	Total Pric
Trade:	22	Plumbing					
		meet Florida Building Code.	·				
Trade:	23	Electric					
760	0	INSTALL A NEW RECEPTACLE-GFCI COU	NTERTOP 20	1.00	EA		*******************************
		Furnish and install a flush mounted, ground fa interrupted, interrupter duplex receptacle and a 20 amp circuit using approved wiring method must be copper. Fish wiring where necessary openings to match surrounding surface as closumaterials and method to meet Florida Building as required by code.	cover plate fed by d. Conductors and repair se as possible.	′			
Trade:	25	Appliances					
8402	i	GENERAL APPLIANCE WORK Reinstall existing garbage disposal. Provide pr and electrical connections. Also provide proper		1.00	GR		
		electrical connections for dishwasher. Repair a match existing as close as possible. Materials meet Florida Building Code.	ffected areas to				
		electrical connections for dishwasher. Repair a match existing as close as possible. Materials	ffected areas to	l	_ocatio	n Total:	**************************************
Location	L	electrical connections for dishwasher. Repair a match existing as close as possible. Materials	ffected areas to			n Total: Ceiling/Floor S	F: 0
Location Spec		electrical connections for dishwasher. Repair a match existing as close as possible. Materials meet Florida Building Code.	iffected areas to and method to				
		electrical connections for dishwasher. Repair a match existing as close as possible. Materials meet Florida Building Code. 8 - Utility Room	iffected areas to and method to	all SF: 0		Ceiling/Floor S	F: 0 Total Price
Spec	#	electrical connections for dishwasher. Repair a match existing as close as possible. Materials meet Florida Building Code. 8 - Utility Room Spec	APPROX. W ATED METAL 6-panel I hinges, striker chain door stop, ylinder deadbolt kset, Yale, ply two coats of sing. Doors that quire painting, door paint Product	all SF: 0		Ceiling/Floor S	
Spec	#	electrical connections for dishwasher. Repair a match existing as close as possible. Materials meet Florida Building Code. 8 - Utility Room Spec Carpentry INSTALL A NEW PREHUNG 6-PANEL INSUL DOOR WITH LOCKS Furnish and install a new pre-hung 1-3/4" thick insulated metal door unit including jamb, casing plate, threshold and weatherstripping and with clinitial view scope and a new entry and single colocketset keyed alike and manufactured by Kwil Weiser or approved equal. Caulk, prime and aphigh quality oil-base paint on door, jamb and cahave a high quality factory paint finish do not requiless requested by the owner. Owner to select color. Door must have N.O.A. from Miami-Dade	APPROX. W ATED METAL 6-panel I hinges, striker chain door stop, ylinder deadbolt kset, Yale, ply two coats of sing. Doors that quire painting, door paint Product	Quantity 1.00	EA	Ceiling/Floor S	
Spec rade: 7	#	electrical connections for dishwasher. Repair a match existing as close as possible. Materials meet Florida Building Code. 8 - Utility Room Spec Carpentry INSTALL A NEW PREHUNG 6-PANEL INSUL DOOR WITH LOCKS Furnish and install a new pre-hung 1-3/4" thick insulated metal door unit including jamb, casing plate, threshold and weatherstripping and with clinitial view scope and a new entry and single colocketset keyed alike and manufactured by Kwil Weiser or approved equal. Caulk, prime and aphigh quality oil-base paint on door, jamb and cahave a high quality factory paint finish do not requiless requested by the owner. Owner to select color. Door must have N.O.A. from Miami-Dade	APPROX. W ATED METAL 6-panel I hinges, striker chain door stop, ylinder deadbolt kset, Yale, ply two coats of sing. Doors that quire painting, door paint Product	all SF: 0 Quantity 1.00	Units EA	Ceiling/Floor S Unit Price	Total Pric
Spec	#	electrical connections for dishwasher. Repair a match existing as close as possible. Materials meet Florida Building Code. 8 - Utility Room Spec Carpentry INSTALL A NEW PREHUNG 6-PANEL INSUL DOOR WITH LOCKS Furnish and install a new pre-hung 1-3/4" thick insulated metal door unit including jamb, casing plate, threshold and weatherstripping and with a linear threshold and weatherstripping and with a linear threshold and weatherstripping and with a linear threshold and manufactured by Kwii Weiser or approved equal. Caulk, prime and ap high quality oil-base paint on door, jamb and ca have a high quality factory paint finish do not reconstructed by the owner. Owner to select color. Door must have N.O.A. from Miami-Dade Approval Section. TO BE DOUBLE METAL DOOR	Approx. Was Approx	all SF: 0 Quantity 1.00 L	Units EA	Ceiling/Floor S Unit Price	Total Price
Spec rade: 7 3160	# 10	electrical connections for dishwasher. Repair a match existing as close as possible. Materials meet Florida Building Code. 8 - Utility Room Spec Carpentry INSTALL A NEW PREHUNG 6-PANEL INSUL DOOR WITH LOCKS Furnish and install a new pre-hung 1-3/4" thick insulated metal door unit including jamb, casing plate, threshold and weatherstripping and with a linear threshold and weatherstripping and with a linear threshold and weatherstripping and with a linear threshold and manufactured by Kwii Weiser or approved equal. Caulk, prime and ap high quality oil-base paint on door, jamb and ca have a high quality factory paint finish do not reconstructed by the owner. Owner to select color. Door must have N.O.A. from Miami-Dade Approval Section. TO BE DOUBLE METAL DOOR 19 - Hall	Approx. Was Approx	all SF: 0 Quantity 1.00 L	EA ocation	Ceiling/Floor S Unit Price Total: Ceiling/Floor SI	Total Pric

Address	: 4531 W 14 Court	Unit: Unit 0	1			
Location	: 9 - Hall	Approx. Wall SF	0		Ceiling/Floor S)F: 0
Spec	# Spec	Qua	ntity	Units	Unit Price	Total Price
Trade: 1	0 Carpentry					
	Furnish and install new frame and ca panel. Repair affected areas to matc possible.					
Trade: 2	3 Electric					
7810	INSTALL A NEW SMOKE & CARBO DETECTORHARD WIRED Furnish and install a UL approved, ce smoke and carbon monoxide combo back-up. Smoke detector outlets in be protected. Materials and method to m	iling mounted, hard wired detector with battery edrooms must be AFCI	1.00	EA		
			L	ocatio	n Total:	
Location:	10 - Bedroom 1	Approx. Wall SF:	0		Ceiling/Floor S	F; 0
Spec #	Spec	Quar	ntity	Units	Unit Price	Total Price
Trade: 10) Carpentry			······································		
2958	INSTALL HORIZONTAL ROLLING V EXISTING WITH FACTORY FINISH Dispose of existing window. Furnish a rolling window to match existing finish screen. If window to be installed is with door in closed position, the window is meet manufactures specification and p Frame and sash finish to match rema imitation marble window sill. A window provided with a U-coefficient and SHG window review approval. (Don't remov Window Inspection has been performe inspection is required. TO BE HIGH IN MATCH THE WINDOWS TO THE RE AS CLOSE AS POSSIBLE WITH TRIN ANYTHING POSSIBLE. MAYBE ASSO ON IT.	nd install a new horizontal Include removable hin 48" of and exterior to be tempered glass. To product control approval, ining windows. Include schedule must be C in order to energy and e window label until Final ed.) Building Permit and IPACT RESISTANT. ST OF THE COMPLEX M MOLDING OR	1.00	EA	n/a	n/a
Frade: 23	Electric					
7566	FURNISH AND INSTALL AN ARC FA INTERRUPTER (AFCI) Furnish and install a new Arc Fault Circuit breakers to protect all bedroom receptacle, light, smoke detector, and coutlets. Materials and method to meet I	cuit Inrerrupter (AFCI) circuits to include wall unit air conditioner	.00	EA	n/a	n/a
7730	INSTALL A NEW CEILING LIGHT FIX Remove and properly dispose of existir Furnish and install a new ceiling light fix new switch and wiring, if necessary. Ma meet Florida Building Code. FOR CLOS	TUREREPLACE 1. ng ceiling light fixture. kture with globe, bulbs, aterials and method to	.00	EA		
7810	INSTALL A NEW SMOKE DETECTOR		nn	ΕΔ		

Address:	4531 W 14 Court Unit:	Unit 01			
Location:	10 - Bedroom 1 Approx. V	väll SF: 0		Geiling/Floor S	iF: 0
Spec #	Spec	Quantity	Units	Unit Price	Total Price
Trade: 23	Electric				
	Furnish and install a UL approved, ceiling mounted, hard wired smoke detector with battery back-up. Smoke detector outlets in bedrooms must be AFCI protected. Materials and method to meet Florida Building Code.				
		l	_ocatio	n Total:	
Location:	11 - Bathroom 2 Approx. V	/ail SF: 0		Ceiling/Floor S	F: 0
Spec #	Spec	Quantity	Units	Unit Price	Total Price
Trade: 10	Carpentry			·	
3346	INSTALL NEW 6 PANEL HOLLOW CORE DOOR IN EXISTING DOOR OPENING W/ LOCKSET Furnish and install a new 1-3/8" thick 6 panel hollow core door with two new 3-1/2" hinges and a new lockset in existing door opening. Lockset to be appropiate for the type of door—privacy or passage. Lockset to be manufactured by Kwikset, Yale, Weiser or approved equal. Repair and fill holes in door jamb and casing. Include threshold and door stop. Caulk, prime and apply two coats of high quality oil-base paint on door, jamb and casing. Doors that have a high quality factory paint finish do not require painting, unless requested by the owner. Owner to select paint color. Materials and method to meet Florida Building Code. INCLUDE REPAIRING DOOR FRAME.	1.00	EA	n/a	n/a
Trade: 22	Plumbing				
7010	REPLACE TOILET Furnish and install a new 2 piece, close coupled, vitreous china water saving commode with a maximum 1.6 gallons per flush manufactured by American Standard, Kholer, Eljer, Briggs or approved equal. Include plastic or pressed wood seat, plastic supply pipe, shut-off valve, flap valve, metal flush handle, flange and wax seal. Top of toilet tank to be no more than 1" from backwall. Coordinate color selection with owner. Materials and method to meet Florida Building Code. MAKE SURE IT DRAINS PROPERLY.	1	EA		
rade: 23	Electric				
7590	INSTALL A NEW RECEPTACLEGFCI BATH Furnish and install a flush mounted, ground fault circuit interrupted duplex receptacle and cover plate feed by 20 amp circuit, adjacent to the basin using approved wiring method. Conductors must be copper. Fish wire necessary and repair openings. To match surrounding finish as close as possible. Materials and method to meet Florida Building Code.	1.00	EA		
		L	ocation	Total:	

Approx. Wall SF: 0

Location: 12 - Bathroom 3

Page 12 of 16

Ceiling/Floor SF: 0

	12 - Bathroom 3 Approx. W	ali ce in	117	Ceiling/Floor S	F: n
Location:	12 - Bathroom 3 Approx: W		17.27 (21.17)	75.00 CT 11101 CT 1771 CT 1771	William Control
Spec #	Spec	Quantity	Units	Unit Price	Total Price
Trade: 10	Carpentry				
3765	INSTALL A NEW VANITY AND A CULTURED MARBLE TOP Dispose of existing vanity. Field measure, furnish and install a new high quality bathroom vanity base cabinet with a cultured marble counter top built by a professional cabinet maker or cabinet manufacturer. New cabinet to match existing. Owner to select plastic laminate. NOTE: Contractor shall repair, paint or match any affected area by the removal or replacement of cabinet and/or counter tops. (All areas, floors, walls, or ceilings affected by cabinet removals must be filled in level of existing surfaces, using comparable materials and sealing of areas to roach and rodent proof, prior to installing cabinets). Replace any rotten drywall prior to cabinet installation. Materials and method to meet Florida Building Code.		LF		
3832	BATH MIRROR Install beveled edge mirror sized at the width of vanity by 36" high. Use adhesive manufactured for this purpose and apply to sound backing.	1.00	SF		
3836	INSTALL NEW BATHROOM ACCESSORY SET Furnish and install a new standard grade 2 bath towel bars, hand towel bar, toilet paper holder, soap dishes, and tooth brush holder. Selection to coordinated by owner and field Specialist.	1.00	EA	n/a	n/a
Гrade: 22	Plumbing	-			
6862	REPLACE BATHROOM Remove existing bathroom fixtures, hardware, plumbing and walls in disrepair and install new fixtures, hardware, plumbing and walls. Repair or replace all damaged wood in floors including floor joist and framed walls. Repair or replace all damaged pipes and all damaged masonry. Materials and method to meet Florida Building Code. INCLUDE REPAIRING LEAK THROUGH LIVING ROOM/KITCHEN CEILING. CHECK IF BATHROOM 2 IS LEAKING AND REPAIR/REPLACE PLUMBING LINES IF NECESSARY.	1.00	EA	n/a	n/a
6875	REPLACE FAUCETLAVATORY SINGLE LEVER Furnish and install a washerless, single control, metal bodied faucet with a pop-up valve and a 15 year drip-free warranty. To be Moen, Price Pfister, Glacier Bay, Dleta, American Standard or approved equal. Include chromed brass shut off valves and trap if required to complete installation. Materials and method to meet Florida Building Code.	1.00	EA		
6966	FURNISH AND INSTALL A NEW PRE-FAB BATH TUB/SHOWER STALL ENCLOSURE Furnish and install a new pre-fab bath tub/shower stall enclosure. Install new water lines, drain lines, and any necessary vents, framing, blocking, shims, and nailers to ensure proper and code approved installation of shower pan and shower stall. Repair or replace room surfaces damaged during construction. Include a new aluminum curtain rod. Repair affected areas to match existing as close as possible. Materials and method to meet Florida Building Code. MATCH EXISTING	1.00	EA	n/a	n/a

Address: 4	531 W/14 Court Ur	nit: Unit 01				
Location:	12 - Bathroom 3 Approx: V			Ceiling/Floor SF: 0		
Spec #	Spec	Quantity	Units	s Unit Price	Total Pric	
Trade: 22	Plumbing					
	AS CLOSE AS POSSIBLE.					
6983	FURNISH AND INSTALL A NEW LEVER TYPE BATHTU AND HANDHELD SHOWER FAUCET		EA	n/a	n/	
	Furnish and install a new lever type washerless bathtub/shifaucet and an adjustable shower head and flexible arm. Fato have a maximum flow rate of 2.5 gallons per minute and least a 1 year warranty. American Standard, Moen Price Pf Glacier Bay, Delta or approved equal. Materials and methomeet Florida Building Code.	aucet at ister,				
7010	REPLACE TOILET	1.00	EA	4		
·	Furnish and install a new 2 piece, close coupled, vitreous cowater saving commode with a maximum 1.6 gallons per fluor manufactured by American Standard, Kholer, Eljer, Briggs approved equal. Include plastic or pressed wood seat, plast supply pipe, shut-off valve, flap valve, metal flush handle, fluor days seal. Top of toilet tank to be no more than 1" from wall. Coordinate color selection with owner. Materials and method to meet Florida Building Code.	ish or iic ange				
Trade: 23	Electric					
7590	INSTALL A NEW RECEPTACLE-GFCI BATH Furnish and install a flush mounted, ground fault circuit interrupted duplex receptacle and cover plate feed by 20 am circuit, adjacent to the basin using approved wiring method. Conductors must be copper. Fish wire necessary and repair openings. To match surrounding finish as close as possible. Materials and method to meet Florida Building Code.		EA	well that the libert was an an extension.		
7731	INSTALL A NEW WALL LIGHT FIXTUREREPLACE Remove and properly dispose of existing light fixture. Furnis and install a new wall mounted with globe, bulbs, install new switch and new wiring, if necessary. Materials and method to meet Florida Building Code.		EA	n/a	n/a	
		F	_ocation Total:			
ocation:	13 - Bedroom 2 Approx	Wall SF: 0		Ceiling/Floor SF	7: 0	
Spec#	Spec	Quantity	Units	Unit Price	Total Price	
rade: 10	Carpentry					
	INSTALL A NEW SINGLE HUNG WINDOW WITH FINISH TIMATCH EXISTING Dispose of existing window. Furnish and install a new window match existing window finish. If window to be installed is with 48" of an exterior door in closed position, the window is to be tempered glass. Include removable scren. To meet manufactures specification and product control approval. Fra and sash finish to match remaining windows. Include imitation marble window sill. A window schedule must be provided with J-coefficient and SHGC in order to energy and window review approval. (Don't remove window label until Final Window	v to in me on	EA	n/a	n/a	

Address: 4531 W 14 Court Uni		nit: U	Unit 01					
Location:		13 - Bedroom 2 Appr	ox. Wa	- Vall SF: 0 Ceiling/Floor SF: 0				
Spe	ec#	Spec		Quantity	Units	Unit Price	Total Price	
Trade:	10	Carpentry						
		Inspection has been performed.) Building Permit and inspis required. TO BE HIGH IMPACT RESISTANT. MATCH WINDOWS TO THE REST OF THE COMPLEX AS CLOS POSSIBLE WITH TRIM MOLDING OR ANYTHING POSSIBLE ASSOCIATION HAS A INFO ON IT.	THE SE AS					
Trade:	20	Floor Coverings						
5955		FURNISH AND INSTALL NEW LAMINATE WOOD FLOORING		1.00	SF			
		Furnish and install a new laminate wood flooring. Owner to provide flooring. Contractor to install as per manufacture specifications. Repair affected areas to match existing as as possible. INCLUDE REMOVING CARPET AND PADDI IN ORDER TO PREPARE AREA FOR NEW LAMINATE WOOD FLOORING.	close					
Trade:	23	Electric						
7566	6	FURNISH AND INSTALL AN ARC FAULT CIRCUIT INTERRUPTER (AFCI) Furnish and install a new Arc Fault Circuit Interrupter (AFC circuit breakers to protect all bedroom circuits to include receptacle, light, smoke detector, and wall unit air condition outlets. Materials and method to meet Florida Building Cod	er	1.00	EA	n/a	n/a	
7810 INSTALL Furnish at smoke de bedrooms		INSTALL A NEW SMOKE DETECTORHARD WIRED Furnish and install a UL approved, ceiling mounted, hard w smoke detector with battery back-up. Smoke detector outle bedrooms must be AFCI protected. Materials and method t meet Florida Building Code.	ts in	1.00	ĒΑ			
				Location Total:				
Location:		14 - Bedroom 3 Approx	k. Wall	SF: 0	Ceiling/Floor SF: 0			
Spec	#	Spec	C	Quantity	Units	Unit Price	Total Price	
rade:	10	Carpentry						
2953		INSTALL A NEW SINGLE HUNG WINDOW WITH FINISH MATCH EXISTING		2.00	EA	n/a	n/a	
		Dispose of existing window. Furnish and install a new windor match existing window finish. If window to be installed is with 48" of an exterior door in closed position, the window is to be tempered glass. Include removable scren. To meet manufactures specification and product control approval. From and sash finish to match remaining windows. Include imitationarile window sill. A window schedule must be provided with U-coefficient and SHGC in order to energy and window review approval. (Don't remove window label until Final Window Inspection has been performed.) Building Permit and inspection for the REST OF THE COMPLEX AS CLOSE POSSIBLE WITH TRIM MOLDING OR ANYTHING POSSIE	nin e ame on th a ew tion IE AS					

Address:	4531 W 14 Court	Unit: Unit 01	American Company				
Location:	14 - Bedroom 3 App	Approx Wall SF; 0 Celling/Floor SF: 0					
Spec #	‡ Spec	Quantity	Units	Unit Price	Total Price		
Trade: 10	Carpentry MAYBE ASSOCIATION HAS A INFO ON IT.				•		
Trade: 20) Floor Coverings						
5955	FURNISH AND INSTALL NEW LAMINATE WOOD FLOORING Furnish and install a new laminate wood flooring. Match a floor finish as close as possible. Contractor to install as p manufacture specifications. Repair affected areas to mat existing as close as possible. INCLUDE REMOVING CAI AND PADDING IN ORDER TO PREPARE AREA FOR N LAMINATE WOOD FLOORING.	er ch RPET	SF				
Trade: 23	Electric		- Liverblood				
7566	FURNISH AND INSTALL AN ARC FAULT CIRCUIT INTERRUPTER (AFCI) Furnish and install a new Arc Fault Circuit Interrupter (AFcircuit breakers to protect all bedroom circuits to include receptacle, light, smoke detector, and wall unit air conditional outlets. Materials and method to meet Florida Building Control of the contro	CI)	, EA	n/a	n/a		
7810	INSTALL A NEW SMOKE DETECTOR—HARD WIRED Furnish and install a UL approved, ceiling mounted, hard smoke detector with battery back-up. Smoke detector out bedrooms must be AFCI protected. Materials and method meet Florida Building Code.	tlets in	EA 	***************************************	-		
8010	CEILING FAN WITH A LIGHT FIXTURE Furnish and install a pull chain operated, 52" ceiling fan wlight fixture using an approved wiring method with copper conductors. Ceiling fan to be directly installed to framing chung on a manufacturer's recommended metal brace. Inclight switch and wiring if necessary. Materials and method meet Florida Building Code.	or Slude	EA ,				
		L	ocation	Total:	The state of the s		
	Unit Total for 4	531 W 14 Court	, Unit U	Init 01:			
	Address Gra	nd Total for 453	1 W 14	Court:			
	Bidder:						

		Proposal						
Case:	S-510	Owner:	ARIEL DE ARMAS					
Bid Number	522	Proj	ect address: 4531 WEST 14 COURT.					
The undersigned submits the bid to the City of Hialeah, Department of Grants and Human Services for Rehabilitation of an existing single family home in accordance with the specifications and in compliance with all local, state and federal laws and regulations as follows:								
	SUBT	OTAL OF BID	\$					
	PROF	IT AND OVERHEAD	\$					
	ТОТА	L COST	\$					
	ALTE	RNATE	\$					
CONTRACTOR'S INFORMATION								
Name of Firm:	***************************************							
Address of Firm o	or Corporation:		-					
Signature of Auth	orized Official:							
Title:								
Telephone:								
Contact Person In Reference To Bid:								
ACCEPTANCE	Yaifizeit/							
RECEIVED BY:_		DATE						
ACCEPTANCE PROPOSAL BY THE HOMEOWNER								
The above prices, specifications and conditions are satisfactory and are hereby accepted as such:								
Date of Acceptance	*	Signature						
Date of Acceptance	•							